

**UPDATABLE PHOTOGRAPH** 

**CATEGORY III CERTIFICATION** 

PTP 770E - Rev7 - 06.10.09



# TEMP-SEA 770

**CE-Type Examination Certificate** N° 0075/014/162/04/07/0123

issued by the approved body nr. 0075 C.T.C. - Rue H. FRENKEL - F-69367 LYON CEDEX 07

**Certificate of conformity of the Quality Assurance System** issued by the approved body nr. 0334

ASQUAL - 14, rue des Reculettes - F-75013 PARIS

This glove conforms to the provisions of Directive 89/686/EEC for protection against chemicals, cold and mechanical risks.

# TEMP-SEA 770

## **DESCRIPTION AND GENERAL PROPERTIES**

Glove made of an acrylic terry knitted with an orange brushed jersey, coated with blue PVC.

#### Curved fingers.

Reference	Finish	External Surface	Minimum Length for all sizes (in cm)*	Thickness in the hand (in mm)*	Sizes available
Temp-Sea 770	PVC spray	Smooth & rough	30	3.15	9 10

<sup>\*</sup> nominal values

Standard packaging:

Single pack / 48 pairs per carton

### "CE"-TYPE EXAMINATION RESULTS




### PROTECTION AGAINST **CHEMICAL**

According to **EN 374** standard. The glove Temp-Sea 770 is liquid proof.



#### PROTECTION AGAINST MECHANICAL RISKS

Levels of performance according to EN 388 standard.





PROTECTION AGAINST COLD Levels of performance according to EN 511:1994 standard.



# PROTECTION AGAINST **MICRO-ORGANISMS**

According to EN 374 standard.

1 2 → permeability (0 or 1) → contact cold (0 to 4) □ convective cold (0 to 4)

Acceptable Quality Level (AQL): 1.5%

Note: The performance levels are determined on the palm area.

57, rue de Villiers - B.P. 190 92205 NEUILLY SUR SEINE Cedex - FRANCE Tél: (33) 1 49.64.22.00 - Fax: (33) 1 49.64.24.29 www.mapa-professionnel.com

MAPA (U.K.) Ltd Berkeley Business Park, Wainwright Road, Worcester - WR4 9ZS - UK

Tel (44) 0 1905 450300 / Fax (44) 0 1905 450350 PROFESSIONNEL

# **TEMP-SEA 770**

### **SPECIFIC ADVANTAGES**

- Acrylic curly fur assuming excellent insulation, downy for better comfort.
- Specially formulated liquid-proof PVC for coldest environmental use (-30°C) and glove flexibility preservation.
- Enhanced grip properties and abrasion resistance.
- Good resistance to oil, grease and hydrocarbon.
- High resistance to ageing by U.V., light and ozone.
- Recommended for persons sensitized to natural rubber proteins.

### MAIN FIELDS OF USE

- Sea and fishing working: fresh products handling.
- Maintenance in wet environments /outsides.
- Warehouses: cold / wet handling.
- Skiing areas: maintenance, machines driving.
- Routine working in liquids (water, oil, hydrocarbons ...).
- Food industries: handling and operations in cold stores.

### **INSTRUCTIONS FOR USE**

For enhanced safety and service life of the gloves:

- Store the gloves in their original packaging protected from humidity and heat.
- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for duration in excess of the measured breakthrough time. Refer to the chemical resistance chart hereafter or contact the Technical Customer Service - MAPA PROFESSIONNEL in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Before taking off the gloves, clean them as appropriate :
  - ☐ in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
  - ☐ in use with acids or alkalies : thoroughly rinse the gloves under running water and rub over with a dry cloth

# **TEMP-SEA 770**

Caution: improper use of the gloves or submitting them to a cleaning or laundering process which is not specifically recommended can alter their performance levels.

- Ensure the inside of the gloves is dry before putting them on again.
- Inspect the gloves for cracks or snags before reusing them.

### **LEGISLATION**

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).