

Ultranitril 492

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (cm)** 32
- **Thickness (mm)** 0.38
- **Wrist** Straight cuff
- **Colour/Color** Green
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10 11
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton
- **Complementary information** Guaranteed without silicone
- available in 2 kind of packaging : individual bag and polybag of 10



PERFORMANCE RESULTS

Certification category 3

CE 0334



AJKL

4101

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 Abrasion resistance
 Blade cut resistance
 Tear resistance
 Puncture resistance



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374



RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 Burning behaviour
 Contact heat resistance
 Convective heat resistance
 Radiant heat resistant
 Resistance to small drops of molten metal
 Resistance to large quantities of molten metal



SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 Convective cold resistance
 Contact cold resistance
 Water permeability

For more details: www.mapa-pro.com

Ultranitril 492

DESCRIPTION AND GENERAL PROPERTIES

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining
- Longer service life: excellent mechanical resistance (abrasion, perforation)

MAIN FIELDS OF USE

Automotive/mechanical industry

- Treating/degreasing metals with solvents
- Machining parts using cutting oil

Construction Industry (Carpenters/Joiners)

- Handling PVC-based glues
- Preparing coatings, varnishes

Construction Industry (Masons / Plasterers)

- Cleaning tools
- Handling oils, solvents, detergents

Local Authorities (Cleaning)

- Handling aggressive chemical products

Local Authorities (Catering Services)

- Cleaning ovens or worktops

Chemical industry

- Manufacture and application of paints and varnishes

Local Authorities (Parks and Public Spaces)

- Plant Treatment Products

Construction Industry (Painters/Decorators)

- Cleaning
- Painting
- Scraping
- Varnishing

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Persons sensitised to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their original packaging protected from light, humidity and heat.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (diluent, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : improper use of the gloves or submitting them to any cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

MADA[®]

PROFESSIONNEL

Ultranitril 492

> Good mechanical resistance and long-lasting chemical protection

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining
- Longer service life: excellent mechanical resistance (abrasion, perforation)

Automotive/mechanical industry

- Treating/degreasing metals with solvents
- Machining parts using cutting oil

Construction Industry (Carpenters/Joiners)

- Handling PVC-based glues
- Preparing coatings, varnishes

Construction Industry (Masons / Plasterers)

- Cleaning tools
- Handling oils, solvents, detergents

Local Authorities (Cleaning)

- Handling aggressive chemical products

Local Authorities (Catering Services)

- Cleaning ovens or worktops

Chemical industry

- Manufacture and application of paints and varnishes

Local Authorities (Parks and Public Spaces)

- Plant Treatment Products

Construction Industry (Painters/Decorators)

- Cleaning
- Painting
- Scraping
- Varnishing



Cat. 3



4101



AJKL



Ultranitril	492
Material	Nitrile
Length (cm)	32
Thickness (mm)	0.38
Wrist	Straight cuff
Colour/Color	Green
Interior finish	Flocked
Exterior finish	Embossed texture
Size / EAN	6 7 8 9 10 11
Packaging	1 pair/bag - 10 pairs/bag - 100 pairs/carton

MAPA
PROFESSIONNEL

www.mapa-pro.com